

# OCS 500N6

## OSCILLATORY WAVE SIMULATOR



### FOR TESTS ACCORDING TO ...

- › ANSI/IEEE C37.90
- › ANSI/IEEE C62.41
- › EN 61000-4-10
- › EN 61000-4-12
- › EN 61000-4-18
- › IEC 60255-22-1
- › IEC 61000-4-10
- › IEC 61000-4-12
- › IEC 61000-4-18
- › IEC 61850-3

### OCS 500N6 - COMPACT TESTER FOR RINGWAVE AND DAMPED OSCILLATORY WAVES

The OCS 500N6 includes test capabilities for ringwave up to 6kV (as per EN/IEC 61000-4-12) and the damped oscillatory waves at 100kHz and 1MHz up to 3kV (as per EN/IEC 61000-4-18).

The Ringwave is a non-repetitive damped oscillatory transient occurring in low-voltage power, control and signal lines supplied by public and non-public networks. Damped Oscillatory Waves are repetitive transients mainly occurring in power, control and signal cables installed in high voltage and medium voltage stations.

The OCS 500N6 can also be used to perform magnetic field tests as required in EN/IEC 61000-4-10 using a magnetic field coil such as the MS 100N.

### HIGHLIGHTS

- › Standalone test generator
- › Includes Ringwave up to 6kV
- › Includes Damped Oscillator Waves up to 3kV
- › Built-in CDN, single phase or three-phase up to 32A
- › Front panel operation

### APPLICATION AREAS

- |  |  |
|--|--|
|  INDUSTRY   |  RESIDENTIAL      |
|  COMPONENTS |  RENEWABLE ENERGY |
|  MEDICAL    |  |
|  BROADCAST  |  |

## TECHNICAL DETAILS

## OCS 500N6 SERIES

## OCS 500N6 MODELS

OCS 500N6.5	With built-in CDN 250V / 16A
OCS 500N6.6	With built-in CDN 250V / 32A
OCS 500N6.7	With built-in CDN 3x440V / 16A
OCS 500N6.8	With built-in CDN 3x440V / 32A

## RINGWAVE AS PER EN/IEC 61000-4-12 AND ANSI/IEEE C62.41

Voltage (o.c.)	250V - 6,000V ± 10%
Rise time	0.5us ± 30%
Oscillation frequency	100kHz ± 10%
Decaying	Ratio of peak 2 to peak 1: 0.4 - 1.1 Ratio of peak 3 to peak 2: 0.4 - 0.8 Ratio of peak 4 to peak 3: 0.4 - 0.8
Source impedance	12ohm and 30ohm ± 20%
Peak current (s.c.)	Max. 500A @ 12ohm or Max. 200A @ 30ohm internally;
Rise time	< 1us
Oscillation frequency	100kHz ± 10%
Polarity	Positive, negative
Repetition rate	1 to 60 transients per minute

## SLOW DAMPED OSCILLATORY WAVES AS PER EN/IEC 61000-4-18

Voltage (o.c.) at HV output	250V - 3,000V ± 10%
Voltage (o.c.) at line output	250V - 2,500V ± 10%
Rise time	75ns ± 20%
Oscillation frequency	100kHz and 1MHz ± 10%
Decaying	Peak 5 to be > 50% of peak 1 value Peak 10 to be < 50% of peak 1 value
Source impedance	200ohm ± 20%
Polarity	Positive, negative
Repetition rate	Max. 50/s for 100kHz and Max. 500/s for 1MHz
Burst duration	At least 2s

## OCS 500N6 SERIES

## TRIGGER CIRCUIT

Release of pulses	Automatic, manual, external
Synchronization	0° - 360°, resolution 1°

## OUTPUT

Direct	Via HV-safety lab connectors
Coupling mode	Line to line Line(s) to ground (PE)
DUT supply 1ph-16A	AC: 250V/16A; 50/60Hz DC: 250V/16A
DUT supply 1ph-32A	AC: 250V/32A; 50/60Hz DC: 250V/32A
DUT supply 3ph-16A	AC: 3x440V/16A; 50/60Hz DC: 250V/16A
DUT supply 3ph-32A	AC: 3x440V/32A; 50/60Hz DC: 250V/32A
CRO trigger	5V trigger signal for oscilloscope

## MEASUREMENTS

Ring wave	Peak voltage and peak current in LCD
-----------	--------------------------------------

## TEST ROUTINES

Quick Start	Immediate start; easy-to-use and fast
Standard Test routines	As per IEC 61000-4-12, Level 1 - 4 Manual Standard Test routine As per ANSI/IEEE C62.41 As per IEC 61000-4-10, Level 1 - 5
User Test routines	Change polarity after n pulses Change coupling after n pulses Change voltage after n pulses Change phase angle after n pulses

## INTERFACE

Serial interface	USB
Parallel interface	IEEE 488, addresses 1 - 30

**TECHNICAL DETAILS**
**GENERAL DATA**

GENERAL DATA	
Dimensions, weight	19"/6HU, approx. 28kg (1-phase) 19"/6HU, approx. 41kg (3-phase)
Supply voltage	115/230V +10/-15%
Fuses	2 x T 2AT (230V); 2 x T 4AT (115V)

ENVIRONMENT	
Temperature	10 °C to 35 °C
Humidity	25 % to 75 %, non condensing
Atmospheric pressure	86 kPa (860 mbar) to 106 kPa (1 060 mbar)

**OPTIONS**

OPTIONS	
CNV 504N5.1	Coupler for 4 signal/datalines for damped oscillatory waves 100kHz and 1MHz as per IEC 61000-4-18, 50V/4A
CNV 504N5.3	Coupler for 4 signal/datalines for damped oscillatory waves 100kHz and 1MHz as per IEC 61000-4-18, 250V/4A
CNV 508N4	Coupler for 4 pairs (8 wires) as per IEC 60255-22-1, 250V/4A
CNV 508N4.1	Coupler for 4 pairs (8 wires) as per IEC 60255-22-1, 250V/16A
MS 100N	Magnetic Field coil for EN/IEC 61000-4-10 application
iec.control	Remote control and documentation software with library of standards

# COMPETENCE WHEREVER YOU ARE



## CONTACT EM TEST DIRECTLY

### Switzerland

EM TEST (Switzerland) GmbH > Sternenhofstraße 15 > 4153 Reinach > Switzerland  
 Phone +41 (0)61/7179191 > Fax +41 (0)61/7179199  
 Internet: www.emtest.ch > E-mail: sales.emtest@ametek.com

### Germany

AMETEK CTS Germany GmbH > Lünener Straße 211 > 59174 Kamen > Deutschland  
 Phone +49 (0)2307/26070-0 > Fax +49 (0)2307/17050  
 Internet: www.emtest.com > E-mail: info.cts@ametek.de

### France

EM TEST FRANCE > Le Trident - Parc des Collines > Immeuble B1 - Etage 3 > 36, rue Paul Cézanne > 68200 Mulhouse > France  
 Phone +33 (0)389 31 23 50 > Fax +33 (0)389 31 23 55  
 Internet: www.emtest.fr > E-mail: info@emtest.fr

### Poland

EM TEST Polska > ul. Ogrodowa 31/35, 00-893 Warszawa > Polska  
 Phone +48 (0)518 64 35 12  
 Internet: www.emtest.com/pl > E-mail: infopolska.emtest@ametek.com

### USA / Canada

AMETEK Compliance Test Solutions > 52 Mayfield Ave. > Edison > NJ 08837  
 Phone +1 (732) 417-0501  
 Internet: www.emtest.com > E-mail: sales.emtest@ametek.com

### P.R. China

E & S Test Technology Limited > Rm 913, Leftbank > No. 68 Bei Si Huan Xi Lu > Haidian District > Beijing 100080 > P.R. China  
 Phone +86 (0)10 82 67 60 27 > Fax +86 (0)10 82 67 62 38  
 Internet: www.emtest.com > E-mail: info@emtest.com.cn

### Republic of Korea

EM TEST Korea Limited > #405 > WooYeon Plaza > #986-8 > YoungDeok-dong > Giheung-gu > Yongin-si > Gyeonggi-do > Korea  
 Phone +82 (31) 216 8616 > Fax +82 (31) 216 8616  
 Internet: www.emtest.co.kr > E-mail: sales@emtest.co.kr

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Subject to change without further notice.